

Confidential Report

Our Ref: 23/61257J/07/23







Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

Date: 2 August 2023

Our Ref: 23/61257J/07/23 Your Ref: 190723

Page: 1 of 5

Client: Westbury Textiles Australia

19 Abrams Street Balcatta WA 6021 Perth

Australia

Job Title: Fire Test on One Fabric Sample

Clients Order Ref:

Date of Receipt: 25 July 2023

Date Test Started: 1 August 2023

Description of Sample: One sample of fabric, which was referenced by the client as;


Coast - Stone

Stated to be: 100% Polyolefin

Work Requested: We were asked to make the following fire test:

IMO FTP Code 2010:Part 8

- * subcontracted test, UKAS accredited
- ** subcontracted test, EN ISO/IEC 17025 accredited
- *** not UKAS accredited









Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk Website: www.bttg.co.uk

Date: 2 August 2023

Our Ref: 23/61257J/07/23 Your Ref: 190723

Page: 2 of 5

Client:

Westbury Textiles Australia

Product Description

Company Name	Westbury Textiles	
FABRIC		
Type of Furniture, e.g., Seat, Sofa, Office Chair, etc;.	Sofa upholstery fabric	
Name and/or Identification of the Product Tested	Coast	
Materials of the Product and its Composite Ratio (i)	100% Polyolefin	
Composition of Weave (ii)	Plain Weave	
Density (Number/Inch) the Number of Threads per Inch in both warp and weft; and	Warp: 44, Weft: 21 threads per inch	
Yarn Number Count	-	
Thickness (mm)	2mm	
Mass per Unit Area (g/m²)	470 GSM	
Colour and Tone (iii)	Stone	
Method and Quantity of Fire Retardant Treatment	No Treatment	
FILLINGS		
Material (Name of Manufacturer, Type Designation)	-	
Type of Filling Material (eg. Foam, Polyester Fibre etc.)	-	
Weight per Unit Volume (kg/m³)	-	
Method and Quantity of Fire Retardant Treatment	-	

- (i) Such as wool, nylon, polyester, etc.
- (ii) Such as plain, weave, twilled.
- (iii) If the product has a pattern, the representative colour shall be described.







Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

Date: 2 August 2023

Our Ref: 23/61257J/07/23 Your Ref: 190723

> 3 of 5 Page:

Client: **Westbury Textiles Australia**

Testing to IMO FTP Code 2010: Part 8

Test for Upholstered Furniture

Conditioning

Immediately prior to testing the samples was placed in indoor ambient conditions for 72 hours and then conditioned in a standard atmosphere of 23±2°C temperature and 50±5% relative humidity for at least 16 hours.

The samples were tested in a room of volume 25m³ and 21°C.

Procedure

The samples was tested in accordance with IMO FTP Code 2010:Part 8 using ignition sources 0 and 1. The sponsor sampled the material and the specimens were cut from the sample received to the dimensions set out in the standard.

The sample was tested over combustion modified polyurethane foam with a density of approximately 34-36kg/m³.

Requirements

No progressive smouldering or flaming within 1 hour of the placement of the cigarette. Ignition Source 0

Ignition Source 1 All progressive smouldering and flaming to cease within 120 sec of removal of the burner tube.

Cigarette Specification (Source 0)

Dimensions (mm) 69mm x 8.0mm

Mass (g) 0.92 Smouldering Rate (mins/secs) 9m 43s







Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

Date: 2 August 2023

Our Ref: 23/61257J/07/23 Your Ref: 190723

> Page: 4 of 5

Client: Westbury Textiles Australia

Results

Cigarette Test - Source 0

Specimen No.	1	2
Extinction Time (smouldering) (min)	25	25
Time of cover split	DNO	DNO
Melting (Yes/No)	Yes	Yes
Dripping (Yes/No)	No	No
Charring (Yes/No)	Yes	Yes
Progressive Smouldering (Yes/No)	No	No
Observations	DNO	DNO
Pass/Fail	PASS	PASS

Result of the Cigarette Test: Pass

Propane Flame Test – Source 1

Specimen No.	1	2
Time of Ignition (s)	5	5
Extinction time of flames after removal of burner (s)	1	1
Time to Cover Split (s)	7	7
Melting (Yes/No)	Yes	Yes
Dripping (Yes/No)	No	No
Charring (Yes/No)	Yes	Yes
Progressive smouldering (Yes/No)	No	No
Observations:		
Pass/Fail	PASS	PASS

Result of the Flame Test: Pass

Acronym

DNP – Did not propagate ES - Escalating smouldering BTE - Burnt to extremities





1066

EC – Escalating combustion DNS - Material did not split ME - Manually extinguished DNO – Did not observe time of event

Shirley® Technologies Limited. Registered Office: Wira House, West Park Ring Road, Leeds, LS16 6QL. A company registered in England & Wales with company number 04669651. VAT Number GB 816764800. BTTG® and Shirley® are trade names of Shirley Technologies Ltd. The supply of all goods and services is subject to our standard terms of business, copies of which are available on request. Our laboratories are accredited to EN ISO/IEC 17025.



Telephone: +44 (0) 113 259 1999 Email: onestopshop@bttg.co.uk

Website: www.bttg.co.uk

2 August 2023 Date:

Our Ref: 23/61257J/07/23 Your Ref: 190723

> 5 of 5 Page:

Client: **Westbury Textiles Australia**

Comment

In our opinion, based on the test carried out on the sample supplied; the results indicate that the sample meets the requirements according to IMO FTP Code 2010:Part 8.

Where required to make a judgement to any pass/fail criteria an estimation of uncertainty of measurement has been taken into account. Under our Policy we have used a non-binary decision rule.

See our decision rules Policy (https://www.bttg.co.uk/about-us/decision-rules-policy/) for further information.

Uncertainty Budget

Measurements: ±2mm Timings: ±2 seconds.

Reported by:..... R Greasley, Laboratory Technician

Countersigned by:P Doherty, Manager

Enquiries concerning this report should be addressed to Customer Services.



