

Confidential Report

Our Ref: 23/6113501/06/23





TESTING • CERTIFICATION • AUDITING		Date: Our Ref: Your Ref:	30 June 2023 23/61135o1/06/23 #120623
		Page:	1 of 5
Client:	Westbury Textiles		
	19 Abrams Street Balcatta WA 6021 Perth Australia		
Job Title:	Fire Test on One Fabric Sample	2	
Clients Order Ref:	#120623		
Date of Receipt:	19 June 2023		
Date Test Started:	30 June 2023		
Description of Sample:	One sample of fabric, which wa	is referenced by the client as	;
	Erba Trevira In /Outdoor - Ivor	У	
Work Requested:	We were asked to make the foll	lowing fire test:	
	IMO FTP Code 2010:Part 7		
	 * subcontracted test, UKAS accredit ** subcontracted test, EN ISO/IEC 17 *** not UKAS accredited 		

Note: This report relates only to the items tested.

Shirley® Technologies Limited. Registered Office: Wira House, West Park Ring Road, Leeds, LS16 6QL. A company registered in England & Wales with company number 04669651. VAT Number GB 816764800. BTTG® and Shirley® are trade names of Shirley Technologies Ltd. The supply of all goods and services is subject to our standard terms of business, copies of which are available on request. Our laboratories are accredited to EN ISO/IEC 17025.





30 June 2023	Date:
23/61135o1/06/23 #120623	Our Ref: Your Ref:
2 of 5	Page:

Client:

Westbury Textiles

Product Description

Company Name	Westbury Textiles		
Type of Material, i.e. Curtain, Drape, etc.	Drape		
Name and/or Identification of the Product Tested	Erba Trevira		
Mass per Unit Area (g/m²)	130 gsm		
Thickness (mm)	1mm		
Colour and Tone (i)	Off White		
Quantity and Number of Any Coating	No Coatings		
Method and Quantity of Fire-Retardant Treatment	No Treatment		
Materials of the Product and its Composite Ratio (ii)	100% Trevira CS Polyester		
Composition of Weave (iii)	Plain weave		
Density (Number/Inch) the Number of Threads per Inch in both warp and weft; and	Warp: 35, Weft: 33 threads per inch		
Yarn Number Count	Unknown		

(i) If the product has a pattern, the representative colour shall be described.

- (ii) Such as wool, nylon, polyester, etc.
- (iii) Such as plain, weave, twilled.



Shirley® Technologies Limited. Registered Office: Wira House, West Park Ring Road, Leeds, LS16 6QL. A company registered in England & Wales with company number 04669651. VAT Number GB 816764800. BTTG® and Shirley® are trade names of Shirley Technologies Ltd. The supply of all goods and services is subject to our standard terms of business, copies of which are available on request. Our laboratories are accredited to EN ISO/IEC 17025.



> Date: 30 June 2023 Our Ref: 23/6113501/06/23 Your Ref: #120623 Page: 3 of 5

Client:

Westbury Textiles

FIRE TESTS ACCORDING to IMO FTP Code 2010:Part 7 Test for Vertically Supported Textiles and Films

Cleaning Procedure

The sample received no pre-treatment as the fabric was stated to be inherently flame retardant.

Conditioning

The sample was conditioned for not less than 24 hours in the standard atmosphere for conditioning textiles of $20\pm$ 5°C and 65 \pm 5% R.H.

Procedure

The sample was tested in accordance with IMO FTP Code 2010:Part 7*. The sponsor sampled the material and the specimens were cut from the sample received to the dimensions set out in the standard.

A 40mm high propane gas flame was applied to the edge of 5 warp and 5 weft specimens for 15 seconds.

The after-flame time, length of char, existence of surface flashing and ignition of cotton waste from drops were recorded.

*Deviation from standard

The test was carried out in a test enclosure to different dimensions to that specified in IMO FTP Code 2010:Part 7. The dimensions of the test enclosure are 1820mm wide x 1220mm deep x 1950mm. The test was carried out in a draught free enclosure.





30 June 2023	Date:
23/61135o1/06/23 #120623	Our Ref: Your Ref:
4 of 5	Page:

Client:

Westbury Textiles

Requirements

The Performance Criteria for Curtains and Drapes states that: Products which show any of the following characteristics obtained by the fire test in appendix 1, shall be considered unsuitable for use as curtains, drapes or free-hanging fabric product for use in rooms containing furniture and furnishings of restricted fire risk as defined in the relevant regulations of chapter II-2 of the Convention:-.

- 1. An after-flame time greater than 5 sec for any of the 10 or more specimens tested with surface application of the pilot flame.
- 2. Burn through to any edge of any of the 10 or more specimens tested with surface application of the pilot flame.
- 3. Ignition of cotton wool below specimen in any of the 10 or more specimens tested.
- 4. An average char length in excess of 150mm observed in any of the 10 or more specimens tested by either surface or edge ignition.
- 5. The occurrence of a surface flash propagating more than 100mm from the point of ignition with or without charring of the base fabric.

If it is found that either or both of the batches of five specimens cut in both warp and weft directions fail to meet one or more of the criteria specified in subparagraphs .1 to .3 and .5 above because of poor performance of only one of the five specimens tested, one complete retest of a similar batch is permitted. Failure of the second batch to meet any of the criteria shall provide the basis for rejection of the fabric for use.

Results

		me time s)		ength m)	-	Flaming to edge (yes or No) Ignition of Cottor Wool from Flamir Drops (Yes or No		n Flaming	Surface Flashing (Yes or No), if yes, Propagation Length (mm)	
	Warp	Weft	Warp	Warp	Weft	Weft	Warp	Weft	Warp	Weft
	0	0	58	52	No	No	No	No	No	No
	0	0	46	53	No	No	No	No	No	No
	0	0	52	50	No	No	No	No	No	No
	0	0	50	55	No	No	No	No	No	No
	0	0	55	52	No	No	No	No	No	No
Mean	0	0	52	55						

Shirley® Technologies Limited. Registered Office: Wira House, West Park Ring Road, Leeds, LS16 6QL.

A company registered in England & Wales with company number 04669651. VAT Number GB 816764800.

BTTG[®] and Shirley[®] are trade names of Shirley Technologies Ltd.

The supply of all goods and services is subject to our standard terms of business, copies of which are available on request. Our laboratories are accredited to EN ISO/IEC 17025.





30 June 2023	Date:
23/61135o1/06/23 #120623	Our Ref: Your Ref:
5 of 5	Page:

Client:

Westbury Textiles

Comment

The results indicate the sample meets the requirements according to IMO 2010 FTP Code, Part 7.

Where required to make a judgement to any pass/fail criteria an estimation of uncertainty of measurement has been taken into account. Under our Policy we have used a non-binary decision rule.

See our decision rules Policy (<u>https://www.bttg.co.uk/about-us/decision-rules-policy/</u>) for further information.

Uncertainty Budget

The overall uncertainty budget IMO FTP Code 2010:Part 7 is as follows:-

Measurements: Duration of Flaming:

±2mm ±2 seconds

Reported by:....

...... B Bland, Technical Customer Service Officer

Countersigned by:..... P Doherty, Manager Enquiries concerning this report should be addressed to Customer Services.



Shirley® Technologies Limited. Registered Office: Wira House, West Park Ring Road, Leeds, LS16 6QL. A company registered in England & Wales with company number 04669651. VAT Number GB 816764800. BTTG® and Shirley® are trade names of Shirley Technologies Ltd. The supply of all goods and services is subject to our standard terms of business, copies of which are available on request. Our laboratories are accredited to EN ISO/IEC 17025.